



Material Safety Data Sheet

Manufacturer's Name Dylon Industries, Inc.	Emergency Telephone No. Call INFOTRAC at 1-800-535-5053
Address 7700 Clinton Road, Cleveland, OH 44144	Other Information Calls 216-651-1300
MSDS Approved By Larry R. Kracker	Date Prepared August 31, 2006

SECTION 1 - IDENTITY

COMMON NAME (used on label) Grade E-1001	HAZARD RATING
PRODUCT CLASS Water based graphite coating	WHMIS Class D-2B

SECTION 2 - HAZARDOUS INGREDIENTS

INGREDIENT	CAS NUMBER	WEIGHT PERCENT	Threshold Limit Value (units)
Graphite	7782-42-5	10-20	Nuisance dust; 15 mppcf/8 Hr.
Amorphous carbon	1333-86-4	10-15	3.5 mg/m ³ (ACGIH)
Biocide	4719-04-4	<0.5	Not established

SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS (Fire & Explosion Data)

Boiling Point 100°C	Specific Gravity (H ₂ O=1) 1.2	Vapor Pressure(mm Hg) Unknown			
Percent Volatile by Volume (%) 80%	Vapor Density (Air=1) >1	Evaporation Rate (Ether=1) <<1			
Solubility In Water Completely miscible	pH 9-12				
Appearance and Odor Gray-black liquid with mild odor.					
Flash Point None	Flammable Limits in Air(% by Volume) NA	Lower ---	Upper ---	Extinguisher Media Material not flammable	Auto-Ignition Temperature NA
Special Fire Fighting Procedures None					
Unusual Fire and Explosion Hazards None					

SECTION 4 - PHYSICAL HAZARDS

Grade E-1001

Stability	Unstable <input type="checkbox"/> Stable <input checked="" type="checkbox"/>	Conditions to Avoid NA
Incompatibility (Materials to Avoid) Avoid contact with strong acids, strong bases and strong oxidizers.		
Hazardous Decomposition Products None known		
Hazardous Polymerization	May Occur <input type="checkbox"/> Will Not Occur <input checked="" type="checkbox"/>	Conditions to Avoid NA

SECTION 5 - HEALTH HAZARDS

Threshold Limit Value See Section 2. Nuisance dust: 10mg/m ³ (total dust), 5 mg/m ³ (Respirable dust)						
Signs and Symptoms of Exposure		1. Acute Overexposure Contact may cause eye or skin irritation.				
2. Chronic Overexposure Unknown						
Medical Conditions Generally Aggravated by Exposure Unknown						
Chemical Listed as Carcinogen or Potential Carcinogen	National Toxicology Program	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	I.A.R.C. Monographs	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>	OSHA	Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>
OSHA Permissible Exposure Limit See section 2		ACGIH Threshold Limit Value See section 2			Other Exposure Limit Used See section 2	
Emergency and First Aid Procedure						
1. Inhalation Remove to fresh air. Obtain medical attention if necessary.						
2. Eyes Flush eyes immediately with plenty of water for 15 minutes; consult a physician.						
3. Skin Wash with warm, soapy water. Wash contaminated clothing before re-use.						
4. Ingestion Do not induce vomiting. Obtain medical attention.						

SECTION 6 - SPECIAL PROTECTION INFORMATION

Respiratory Protection (Specify Type) See sections 2 & 5. Approved dust/mist respirator in area where respirable particles exceed TLV for nuisance dust.				
Ventilation Normal plant ventilation	Local Exhaust Recommended	Mechanical (General) Recommended	Special ---	Other ---
Protective Gloves Work gloves. Rubber or neoprene (if needed).			Eye Protection Safety goggles	
Other Protective Clothing or Equipment Normal work apparel				

SECTION 7 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions to be Taken in Handling and Storage Respiratory protection should be used when entering areas containing respirable dust/mist in concentrations above the threshold limit value (TLV) for nuisance dusts.	
Other Precautions Keep from freezing. Keep containers closed until used. Avoid contamination with dirt and other foreign matter.	
Steps to be Taken in Case Material is Released or Spilled Treat as a lubricating oil spill. Absorb with clay or diatomaceous earth.	
Waste Disposal Methods Dispose of in accordance with local, state and federal regulations.	